

Polarbar minibars

Quality engineered with absorption cooling technology, this super quiet unit will please your guests all day and all night! Stylishly designed, with exceptionally generous internal cabinet space, these minibars are the perfect complement to a great hotel room.

Standard features include a lock and an inside light. These minibars are available in three different sizes with two types of glass doors as an option, for better product visibility and increased guest use.

STANDARD FEATURES

- : Stocking capacity of up to 38 facings
- : Transparent door racks for high visibility
- : Removable shelving for easy cleaning
- : Thermal insulation manufactured with cyclopentane.
- : Fully automated defrost and easily adjustable thermostat
- : Strong door hinges convertible left to right
- : All-round magnetic seals to keep the door perfectly shut
- : Integrated door handles
- : Interior LED light
- : Lock (can be deactivated)
- : Available sizes are 30, 40 and 60L
- : 3 different door options available
- : ISO 9001 2008 / IS 14001 2004 CE

OPTIONAL FOR STANDARD MODEL:

- : Black plastic framed glass door
- : Aluminum framed glass door



PB Standard (Black Framed Glass Door)



PBD 42 (Drawer Unit)

NEW DRAWER UNIT

- : Stocking capacity of up to 38 facings
- : Transparent door racks for high visibility
- : Removable shelving for easy cleaning
- : Thermal insulation manufactured with cyclopentane.
- : All-round magnetic seals to keep the door perfectly shut
- : Interior LED light
- : Lock (can be deactivated)
- : Available size is only 42L
- : Strong drawer slides, drawer can be easily removed
- : Integrated door handles and bespoke wood panel options
- : Can be inserted or stand-alone (Drawer)
- : ISO 9001 2008 / IS 14001 2004 CE

ASSA ABLOY

ASSA ABLOY Hospitality

The global leader in
door opening solutions

SPECIFICATIONS

	Polarbar 30 (PB 30)	Polarbar 40 (PB 40)	Polarbar 60 (PB 60)	PolarbarDrawer Unit (PBD 42)
Net Capacity Litres Cu.ft.	30 1.06	40 2.19	60 2.19	42 1.48
Dimensions H x W x D mm inches	520x400x425 20,5x15,88x16,7	520x400x475 20,5x15,88x18,7	526x482x465 21,7x18,97x17,91	418 – 550 – 490 16 ^{1/2} – 21 ^{2/3} – 19 ^{2/7}
Watts (W)	65	65	85	65
Voltage (V)	220/240	220/240	220/240	100/220
Energy Consumption (kWh/24h)(1)	0,85	0,90	0,90	0.80
Net weight (kgs) (lb)	15,5 34,1	16,5 36,3	17,0 38,8	18.4 40.56
Certification	ISO 9001 2008 / IS 14001 2004 CE (ISO/CE/ETL/ERP/WEEE/ROHS)			

ADDITIONAL INFORMATION

- : Ventilation requirements for built-in minibars: a channel for air circulation is imperative for ventilation and operation. A minimum open area of 31 in2 (200 cm2)
- : Specifications may change without notice due to continuous product development.
- : Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature in compliance with EN ISO 7371

POLARBAR MODELS



PB Standard 30, 40 and 60 (Black Solid Door)



PB A 30 and 40 (Black Plastic framed Glass Door)



PB AGD 30, 40 and 60 (Aluminum Glass Door)



PBD 42 (Drawer Unit)