

RFID Encoder and Updater

This highly qualified and sophisticated RFID encoder and updater is embedded into one single device. It is designed with functionality, reliability and durability in mind.



Features

- : For encoding, verification and auto-update of RFID cards.
- : Card standards: ISO 14.443A/B and ISO 15.693.
- : Sound signals.
- : Several possibilities for powering via USB, via PoE (power over Ethernet) or external power.
- : Configurable through web interface.
- : Horizontal (table) or vertical (wall) mounting.
- : Color display.

Technical Data

	SPECIFICATIONS
Dimensions (W x H x D)	83,3 x 152,0 x 42,2 mm $3\frac{9}{32} \times 5\frac{31}{32} \times 1\frac{21}{32}$ in
Dimensions card holder (W x H x D)	88,7 x 85,8 x 48,0 mm $3\frac{1}{2} \times 3\frac{3}{8} \times 1\frac{57}{64}$ in
Encoder material	ABS UL 94V - 0
Card holder material	PC UL 94V - 0, semitransparent
Automatic adjustment	10 to 100 Mbit/s networks when connected to the server via TCP/IP
Temperature range	Intended for indoor use only; +5°C to +50°C.
Relative humidity	10-90 %; non-condensing
Power	5V DC, 500 mA
Software requirements and compatibility	Visionline: Application server version 1.12.0 or higher. Vision: Compatible with all Vision RFID locks. 2800: Supported in SW version 1.2.0 and higher.

ASSA ABLOY Hospitality

www.assaabloyhospitality.com

ASSA ABLOY

The global leader in
door opening solutions