Elsafe ZenithElectronic Safes

The choice of in-room electronic safes becomes easy when you can choose Zenith to secure your users' belongings. Zenith is advanced and economical security, with the industry's leading audit trail system that allows you to print out comprehensive report on all safe activities.

Zenith is available in many sizes and models to complement your room regardless of style and need.

FEATURES

- : Industry leading audit trail (500 events)
- : Flash memory
- : Reprogrammable configuration
- : ADA compliant telephone style keypad
- : 4-digit code
- : LED display for clear visible numbers
- : Green backlit keypad
- : Internal light
- : Push button to lock door
- : Powered with five (5) AA batteries
- : Low battery warning
- : Easy external battery change
- : Spring loaded door
- : Accommodates up to 17" laptop in certain models
- : Serviced by computerized service device with unique service code
- : Supports IR communication
- : Anti-tamper labyrinth
- : Internal carpet
- : Unique triangular locking bolt reinforcement
- : Easy maintenance
- : 18 mm solid bolt locking mechanism

Optional features

- : Anti tamper switch
- : Wireless RF online communication upgrade (requires online network).
- : Rental mode by activation code
- : Power outlet inside the safe







ASSA ABLOY

The global leader in door opening solutions

SPECIFICATIONS



SafeLink Software

SafeLink software is the ultimate tool to commission, maintain, and service Elsafe safes.

PinKev

PinKey is a compact electronic PIN code protected key to securely override and service Elsafe safes.



Measurements		Zenith 27	Zenith 43	Zenith Wide	Zenith In-Wall	Zenith Floor
Outside H/W/D	mm	191/354/270	191/354/432	191/460/417	469/418/170	536/355/457
Incl. keyboard	in	7 ^{33/64} /13 ^{15/16} /10 ^{41/64}	7 ^{33/64} /13 ^{15/16} /17	7 ^{33/64} /18 ^{3/8} /16 ^{27/64}	1812/1612/658	21 ^{1/8} /14/18
Inside H/W/D	mm	188/351/200	188/351/361	188/457/345	400/350/95	500/349/371
	in	7 ^{3/8} /13 ^{13/16} /7 ^{7/8}	7 ^{3β} /13 ^{13/6} /14 ^{7/32}	7 ^{3/8} /18/13 ^{19/32}	15 ^{3/4} /13 ^{3/4} /3 ^{3/4}	19 ^{11/16} /13 ^{3/4} /14 ^{5/8}
Door dimensions H x W	mm in	140/295 512/11 ⁵⁸		140/400 512/1534	390/300 15 ^{1/3} /11 ^{4/5}	460/226 18 ^{1/8} /8 ^{15/16}
Internal volume	litres	13	24	31,5	17,5	66
	cu ft	0,46	0,84	1,11	0,61	2,33
Weight	kg	7,8	10	12	20	36,2
	Ib	16,8	21,6	26,5	44	79,8

H/W/D: Height/Width/Depth

Outlets

Optional internal power outlet in different types (US, EU and UK).



Drop safe

Floor safe with a slot and slope in the ceiling on the safe.



	Color Option 1	Color Option 2	Color Option 3
Body color	Black Gray RAL 7021	Ivory RAL 1015	White RAL 9003
Frame color	Black Gray RAL 7021	Ivory RAL 1015	White RAL 9003
Front	Black Gray RAL 7021	Ivory RAL 1015	White RAL 9003

Door Body Frame & Backwall

- : Steel thickness 27/43 4mm 1.5 mm 2 mm
- : Steel thickness Wide 5 mm 1.5 mm 2 mm
- : Steel thickness In Wall 6 mm 2 mm 2 mm
- : Steel thickness Floor 8 mm 3 mm 3 mm
- : Fastening method 27/43/Wide Bottom 4 holes, Backwall 3 holes
- : Fastening method In Wall Sidewalls 4 holes (into wall studs)
- : Fastening method Floor Mounting plate 3mm, 4 bolts