



Handheld Service Terminal

Service unit for locks and safes

A handheld service terminal used for uploading programs and data transfer to electronic door locks and/or safes. This service terminal synchronizes programming between the PC server and the locks and/or safes.

Features

- : Aesthetically pleasing, with modern design.
- : Up to 1 meter drop crash tested.
- : Touchscreen.
- : Flash RAM memory.
- : 3 various power saving modes; full-, reduced-and power down mode.
- : IR communication with 1 meter range
- : USB interface.
- : Charged through mini-USB connector or AC-adapter.
- : Windows® CE 5 platform.
- : 7 days minimum standby time.
- : Short charging time (80%-1h, 100%-2h).
- : Backwards compatible with all existing VingCard and Elsafe cards and adapters.
- : Field upgradable application and operating system firmware through USB or SD slot.

Technical Data

| Dimensions (LxWxD): | 155x90x20 mm 6 7/64" x 3 35/64" x 25/32" in |
|------------------------|---|
| Voltage: | 100-250 VAC 50/60 Hz |
| Battery capacity: | Minimum operating time : 7 hours Minimum standby time : 7 days |
| Charging time: | 80% - 1 hour, 100% - 2 hours |
| Operation temperature: | 0°C to +40°C |
| Storage temperature: | -30°C to +60°C |
| Humidity resistance: | 10% to 90% non-condensing |
| Ingress Protection: | IP 42 |
| Connector: | Mini USB |
| Slots: | SD Card |
| Standards: | Meets the European EMC directive 89/336/EEC of emissions and immunity: <ul style="list-style-type: none"> • EN 61000-6-3 : 2001 • EN 61000-6-4 : 2001 • EN 61000-6-1 : 2001 • EN 61000-6-2 : 2001 |

